

D621 Grated Step Urinal

A grated urinal with a lower standing area. Choose the length and outlet position, then confirm whether your order includes a front step, end panels or joiners. These options are not automatically included.

Product selection

Item	Specification and selection
Model	D621 Grated Step Urinal
Body material	1.2 mm 304 stainless steel. 316 also available on request.
Finish	Brushed #4 stainless steel.
Length	900 to 5500 mm; custom configurations by enquiry.
Configuration	Urinal body and grated lower area
Outlet position	Left hand / centre / right hand / custom. Dimension from a named end.
Options	Front step, end panels and joiners are optional. Confirm each item in the quotation.
Inlet arrangement	Concealed or exposed inlets, as selected for the installation.

Dimensions and interfaces

Confirm the floor interface, finished floor level and any front step against the project drawing.

Use the existing Marko D621 dimensioned specification alongside this sheet. Confirm the section profile, installation levels and outlet location on the project drawing; the selected length alone does not define these interfaces.

Flushing equipment and inclusions

Specify the cistern or flushing system required and identify any equipment supplied by others. Confirm the urinal, inlet connections, waste assembly and optional components included in the quotation. Equipment selection must suit the project and available services.

This sheet supports product selection. It does not establish a flushing volume, certification, accessibility compliance or suitability for a particular installation.

Dimensions and Ordering

All dimensions in mm | Identify the end used for outlet measurements

Your project schedule

Information	Requirements to confirm
Product and quantity	D621 Quantity: ____
Length and site opening	Overall length: Clear opening: ____ ____
Material	304 / 316
Outlet	Position: Dimension from named end: ____ ____
Installation	Floor level, recess and section profile: ____
Ends and joins	Built-in / exposed ends: Join locations: ____ ____
Selected options	Front step: End panels: Joiners: ____ ____ ____
Flushing equipment	System and model: Supplied by: ____ ____
Plumbing interfaces	Inlet arrangement: Waste connection: ____ ____
Supply scope	Included components: Items by others: ____ ____

How to specify

Marko Stainless & Aluminium D621 grated step urinal, [quantity], [overall length], in 1.2 mm [304 or 316] stainless steel with brushed #4 finish. Provide [outlet position from named end], [selected end treatment and options] and [confirmed flushing equipment and supply scope]. Coordinate installation and services to the confirmed project drawing. Refer to MARKO-D621-SG R02.

What to send with your enquiry

Send a dimensioned plan or site sketch showing the opening, adjoining walls, finished floor level and existing services. Include access restrictions and delivery requirements for long units. List any required project standards or equipment documentation so these can be checked for the selected configuration.

Before ordering

Confirm the final dimensions, installation interfaces, outlet and inlet locations, selected options and equipment inclusions. This customer selection sheet supplements the original technical specification; it is not an installation or fabrication drawing.

Images are for visual reference only; actual products and selected options may vary. Contact Marko for custom configurations and product-specific care information.