TG96 Trough Guard - Project

Usually supplied pre-fitted to B619 or D619, or separately for a measured retrofit. Request a fit review for your standard or made-to-order trough. Marko can discuss adjustments to suit the project.

Use this form to describe the selected trough, guard fit and opening clearances. Include photographs for an existing installation. All dimensions in mm.

Project / site

Your reference / quote reference

Customer / company

Contact name / email / phone

Supply - choose ONE: pre-fitted / separate retrofit

Existing or new trough model / quantity

Actual trough length / requested guard length (mm)

Actual trough width / depth (mm; label each)

Rim / rear-edge profile and drawing revision

Tile lip / down return / splashback height (mm)

Bubbler / bottle filler models and positions

Available closed / fully open clearance (mm)

Guard fit is project-specific. Confirm actual trough and rear-edge dimensions, wall clearance, and every tapware projection in both open and closed positions. Provide the trough model or a measured drawing with photographs.

ACCREDITED

TG96 Trough Guard - Scope

Use the same project/reference as page 1. Attach marked plans, original profile references and clear photographs where relevant. The quotation and confirmed project drawing define the final order.

Project / site

Your reference / quote reference

Guard grade / thickness / finish requested

Support materials / brackets / existing fixings

Hinge arrangement / opening clearance (mm)

Lock / keying / hardware supply request

Fixing-hole / mounting-interface details (mm)

Tapware / waste / service access to retain

Lid / ends / hinges / hardware inclusions

Site installation responsibility / access

Photos / measured drawing references

Delivery location / requested timing

Other adjustments / project criteria / questions

TG96 is not a universal fit. Marko will confirm compatibility, guard dimensions, feasibility and inclusions in the quotation and project drawing. This enquiry does not certify a load, security or accessibility rating.

ASSDA ACCREDITED